

# TRIDENTE®

**2025 CATALOG**

## **CAULKING GUNS**

2025 CATALOG – CAULKING GUNS



[tridentetools.com](http://tridentetools.com)



# CAULKING GUNS

## SINGLE COMPONENT APPLICATOR CAULKING GUNS

- 360° rotary type handle
- Heat Treatment: pushing rod
- Two heat treatment: gripper plates
- Aluminum alloy handle / metal trigger
- Spot & reinforced argon welding carriage
- With built-in puncture tool
- Patented no tigger gaps design



| CAPACITY (ml) | THRUST RATIO | PITCH (mm) | WEIGHT (kg) |
|---------------|--------------|------------|-------------|
| 856           | 26:1         | 3          | 1.09        |
| 310           | 26:1         | 3          | 0.84        |
| 856           | 12:1         | 7          | 1.04        |
| 310           | 12:1         | 7          | 0.78        |

# CAULKING GUNS

## SINGLE COMPONENT APPLICATOR CAULKING GUNS

- 360° rotary type handle
- Heat Treatment: pushing rod
- Two heat treatment: gripper plates
- Aluminum alloy handle / metal trigger
- Riveted carriage
- Patented quick switch
- 7:1 to 14:1 thrust ratio system



| CAPACITY (ml) | THRUST RATIO | PITCH (mm) | WEIGHT (kg) |
|---------------|--------------|------------|-------------|
| 310           | 7:1 / 14:1   | 12 / 6     | 0.78        |

## SINGLE COMPONENT APPLICATOR CAULKING GUNS

- 360° rotary type handle
- Heat Treatment: pushing rod
- Two heat treatment: gripper plates
- Aluminum alloy handle / metal trigger
- High-performance drive [Easy on hand]
- Suitable for cold weather and High viscosity materials
- Patented impact-resistant polypropylene casing
- Rubber coating on grip and trigger
- LOGO print screen or label
- Patented 2-in-1 convertible rod puller or ladder hook puller



| CAPACITY (ml) | THRUST RATIO | PITCH (mm) | WEIGHT (kg) |
|---------------|--------------|------------|-------------|
| 310           | 36:1         | 3          | 0.82        |

SACHET APPLICATOR  
CAULKING GUNS

- Heat Treatment: pushing rod
- Two heat treatment: gripper plates
- Aluminum alloy handle / metal trigger / nylon with glass fiber handle and trigger
- Anodised aluminium barrel
- With built-in puncture tool
- Patented quick fit & toolless plunger
- Patented no tigger gaps design
- W/ plunger rod hook
- Designated colors are available on front and back caps, handles



- 360° rotary type handle
- Heat Treatment: pushing rod
- Two heat treatment: gripper plates
- Aluminum alloy handle / metal trigger
- Spot & reinforced argon welding carriage
- With built-in puncture tool
- Patented no tigger gaps design

DUAL COMPONENT  
APPLICATOR CAULKING GUNS

| CAPACITY (ml)    | THRUST RATIO | PITCH (mm) | WEIGHT (kg) |
|------------------|--------------|------------|-------------|
| 200 (1:1 / 2:1)  | 26:1         | 3          | 1.16        |
| 400 (1:1 / 2:1)  | 26:1         | 3          | 1.34        |
| 600 (1:1 / 2:1)  | 26:1         | 3          | 2.04        |
| 900 (2:1 / 10:1) | 26:1         | 3          | 2.58        |
| 1500 (1:1)       | 26:1         | 3          | 3.22        |



| CAPACITY (ml) | THRUST RATIO | PITCH (mm) | WEIGHT (kg) |
|---------------|--------------|------------|-------------|
| 600           | 12:1 / 24:1  | 7.5 / 4.5  | 0.95        |
| 600           | 26:1         | 3          | 1.42        |
| 600           | 12:1         | 7          | 1.38        |